

WILTON MANORS, Island City

2020 WILTON DRIVE, WILTON MANORS, FLORIDA 33305

COMMUNITY DEVELOPMENT SERVICES

(954) 390-2180 FAX: (954) 567-6069

DRIVEWAY/WALKWAY/PATIO/ DECK/POOL DECK

Life's Just Better Here

DRIVEWAY/ WALKWAY/ PATIO/ DECK/POOL DECK

This checklist is designed to expedite the permit application processing by ensuring that all required documentation is submitted with your application.

_		_			
$\mathbf{D} \mathbf{E} C$	α	ONIT INTO	DEDIME	APPLICATION($C \setminus$
$\Gamma \Gamma \Lambda$	ハコトロコン			APPLICATION	. 71

Building
Plumbing (if applicable)
Electrical (if applicable)

MINIMUM PLAN SUBMITTAL

One (1) copy of survey showing an original seal prepared within the last (2) years.
One (1) copy of signed and sealed drawings. (if applicable)
One (1) copy of a completed "Impervious & Pervious Space Calculation" form.
One (1) copy of Homeowner's Association Approval, if required.
Owner/Builder Affidavit if installed/constructed by Owner.
One (1) copy of approval by Broward County Environmental Protection & Growth Management
Department. (if applicable)

SPECIFIC REQUIREMENTS

The contractor is responsible for having underground utilities located, and having water meters relocated. The contractor is liable for any damage to utility lines, sidewalks and roadways.

Specifications and Turnouts:

- O Driveways to residences shall be paved with <u>asphalt</u>, a minimum of nine (9) feet wide, to the same specifications as secondary roads and streets except that subgrade stabilization shall not be required. Driveways shall join (abut) the road or street pavement with returns (turnouts) having six (6) feet radii or with wedges having four (4) foot minimum dimensions.
- O Driveways to residences may be paved with <u>concrete</u> four (4) inches thick, reinforced with fiber or ten (10) gauge 6x6 wire mesh; driveways and turnouts in right-of-way areas are to be six (6) inch thick concrete or four (4) inch thick fibered concrete. All other requirements remain the same.
- O Driveways to residences may be constructed of <u>paver bricks</u> or paver blocks. The plans submitted must contain details of the subgrade, the type, thickness and degree of compaction of the base material, and the poured concrete edging to hold the pavers in place. Other requirements remain as stated in Items 1 and 2 above.
- O Driveways to commercial properties shall be paved not less than ten (10) feet wide (except turnouts to gasoline services stations shall be paved not less than thirty (30) feet wide), to the same specifications as primary roads and streets. They shall join (abut) the road or street pavement with returns (turnouts) having eight (8) feet radii or wedges having six (6) foot minimum dimensions.

Elevation and pitch of existing swales must not be changed by any proposed work.

For commercial and multi-family properties, a field density report will be required for the rock base.

A permit is required for seal-coating driveways for multi-family and commercial structures.

NOTE: City is not responsible for the repair of asphalt, brick pavers, or concrete installed by homeowner in right-of-way.

INSPECTIONS

Inspections must be submitted online prior to **4:30 PM** for the next business day.

REVIEW STOP(S)

Building

Zoning

Public Utilities

Plumbing (if applicable)

Electrical (if applicable)

^{*}Please note that this checklist is not intended to be all-inclusive. Due to changes in codes, regulations, and ordinances, other requirements may apply.



WILTON MANORS, Island City

2020 WILTON DRIVE, WILTON MANORS, FLORIDA 33305

COMMUNITY DEVELOPMENT SERVICES

(954) 390-2180 FAX: (954) 567-6069

IMPERVIOUS & PERVIOUS SPACE CALCULATION

IMPERVIOUS & PERVIOUS SPACE CALCULATION

TYPE OF IMPROVEMENT:	\square ADDITION	□ CIVIL &SITE	□ DECK	□ DRIVEWAY	□ PATIO
	□ POOL	□ SHED	□ SLAB	□ SPA	□ WALKWAY
Owner Name:					
Contractor Name:					
Job Address:					
					AREA (SQ. FT.)
TOTAL LOT AREA:					
PRIMARY BUILDING (HOU	SE):				
PORCHES/PATIOS/WALKW	WAYS/CONCRET	E SLABS (NO WO	OD DECKS	5)	
DRIVEWAYS (CIRCULAR/B	ACKOUT):				
POOL:					
OTHER:					
		TOTAL IM	IPERVIOUS	S AREA =	
TOTAL IMPERVIOUS AND			-	•	
[(TOTAL IMPERVIOUS/TOTAL LOT AREA) X 100= IMPER		PERVIOUS %]	•	vious % =	
			Pervio	us % =	
I certify that all foregoing infoliaws regulating construction a		ite and that all wor	k will be do	ne in compliance	e with all applicable
Property Owner Signature (requ	ired)	Da	te	_	
Contractor Signature			te	_	

NOTE: RS-5 Single Family Zoning: 50% of the entire property can be impervious.